



An Ingersoll Rand Business

14 GPM: D14MZ10VFBPHY

PRODUCT DESCRIPTION

The Dosatron D14MZ10VFBPHY is water-powered so no electricity is needed and it includes a union for easy installation into the Nutrient Delivery System.

PRODUCT SPECIFICATIONS

Dilution Range:	1:100 to 1:10 (1% to 10%)
Injection Range mL:	37.5 to 375 mL/gal
Injection Range tsp:	7.5 to 75 tsp/gal
Water Flow Range:	0.05 to 14 GPM
Operating Pressure Range:	7 to 85 PSI
Available Housing Materials:	Polypropylene
Other Options:	Viscous
Dimensions:	19 1/18" x 6 5/16"
Weight:	6 lbs
Connection Size:	3/4" NPT
Maximum Temperature:	104° F
Included Accessories:	6' clear suction tube, strainer, bypass, weight, mounting bracket and quick start guide
Recommended Accessories:	200 mesh filter, check valve, pressure regulator, flow restrictor



MAINTENANCE KITS

Mini-Maintenance Kit (Part #: PJDI122MINI-H) - For regular maintenance

Injection Seal Kit (Part #: PJDI122) - For yearly maintenance

Injection Seal Kit for Viscous (Part #: PJDI122V) - For yearly maintenance

Rebuild Kit (Part #: MKD14MZ10) - Extends the life of your Dosatron

Call 800-523-8499 to order the Dosatron for your specific application



DOSATRON®

An Ingersoll Rand Business

14 GPM: D14MZ10VFBPHY

Lo-Flo Nutrient Delivery System Installation



The Nutrient Delivery System is customizable,
more dosers can be added as needed.

NOTE: Installation illustrations are to be used as a reference guide only.

Dosatron International
2090 Sunnydale Blvd. • Clearwater, FL, USA
800-523-8499 • www.dosatron.com

Dosatron International, Inc. is an industry leader in water-powered, proportional chemical injectors. Dosatron products are manufactured according to ISO 9001:2000 and ISO 14001:2004 standards.