

11 GPM: SD25AL4N

PRODUCT DESCRIPTION

The Water-Powered Dosatron **SmartDosing** (SD25AL4N) is used in the animal health sector to provide innovative management of drinking water treatments through security, monitoring and traceability. This unit has a flow of 0.04 to 11 GPM and an injection range of 0.8% to 4%.

PRODUCT SPECIFICATIONS

Dilution Range:	0.8% to 4%
Water Flow Range:	0.04 to 11 GPM
Operating Pressure Range:	4.3 to 85 PSI
Dimensions:	21" x 13 4/5"
Weight:	10 lbs
Connection Size:	3/4" NPT
Maximum Temperature:	104° F



Call 800-523-8499 to order the Dosatron for your specific application



DOSATRON®

An Ingersoll Rand Business

11 GPM: SD25AL4N

SMARTDOSING FEATURES

Security: monitor and secure your treatments in real-time

Optimization: optimize treatment duration and volumes

Traceability: follow up your treatment data and the proper functioning of your SmartDosing with just a few clicks

Time saving: simplify your calculations, come back and renew your treatment tank just in time and avoid paperwork

Connect to your computer, controller or install as stand-alone

Adapts to your breeding configuration and allows real-time monitoring

Dosatron International
2090 Sunnydale Blvd. • Clearwater, FL, USA
800-523-8499 • www.dosatron.com

Dosatron International, LLC. is an industry leader in water-powered, proportional chemical injectors. Dosatron products are manufactured according to ISO 9001:2000 and ISO 14001:2004 standards.