

Dilution™ SOLUTIONS

To order call 1-800-451-6628

eMP

SPECIFICATIONS

The **eMP** Livestock Water Treatment metering pump is the perfect answer for your water treatment needs. It is simple to use, highly reliable, and compact in size.

- Flow – 0.26 GPH (1 LPH)
- Max Pressure – 145 PSI (10 BAR)
- Weight – 6.7 lbs
- Stroke Output (ML) – 0.09 at 145 PSI (10 BAR)
- Max Pulses Per Min. – 180
- Mount Type – Wall Mount
- Voltage – 120V

eMP features:

Automatically adjusts injection speed to the water flow for proportional delivery

Dual scale dial for easy stroke adjustment

Operates with 1 pulse per 1 gallon (1PPG) or 1 pulse per 10 gallon (1PP10G) water meter

Long lasting, unique one-piece, Teflon® (PTFE) diaphragm design

Self-priming pump head with manual air bleed for fast priming

No squeeze tubes that can break

PVDF solenoid head for enhanced chemical resistance

IP65 acid resistance housing

Turns off automatically when the chemical container is empty

Pump will turn OFF if pressure exceeds 145 PSI



 **ETATRON**

eMP Wetted Parts

Pump Head	PVDF
Diaphragm	PTFE (Teflon®)
Seals	TFE/P (Aflas®)
Valves	Ceramic Ball
Discharge Tubing	PE (Polyethylene)
Suction Tubing	PVC